


SR10010F Series

Application

- ✓ Video, Audio, Home appliance, Precision apparatus,
Automotive, Musical instruments, Industrial control, Others

Feature

- ✓ Up to 6 positions Horizontal type switches with optional metal shafts.



■Specification

Rating	16V DC 0.1A
Contact Resistance	50 mΩ Max.
Rotational Torque	400 ± 200 gf.cm
Operating Life Cycle (Without Load)	10,000 cycles

■How to order

SR10010F – 0102 – 15R0A – C7 – N

[Model](#)

Number of Pole & Position
Ex. 0102 – 1 pole 2 positions
0402 – 4 poles 2 positions

[Shaft Type](#)

[Flat Cut of Shaft Direction](#)

Timing:

Order Code	Description
N	Non-shorting (break-before-make)

Bushing Type:





Order Code	Bushing Length	Bushing Diameter
C7	6mm	M7*0.75

ALPHA





SR10010F Series

■ Shaft Type

Flat Cut of Shaft Direction

Order Code	(L)KOA	(L)FOA	(L)SOA	(L)ROA
Shaft Type	18 Teeth knurled	Flat shaft	Slotted shaft	Round shaft
Dimensions				
Standard Shaft Length (L)	15, 20, 25, 30			

■ Flat Cut of Shaft Direction

Code	Flat Cut of Shaft Direction	0°	30°	45°	90°
0	0°				
1	30°				
2	45°				
5	90°				

Design and specifications presented here are for the standard parts only. Please kindly contact us for your special requests and ask for the current technical specifications before purchase and/or use.

[Back to top](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Alpha (Taiwan):

[SR10010F-0106-20F0B-C7-N](#) [SR10010F-0205-20F0B-C7-N](#) [SR10010F-0202-20F0B-C7-N](#) [SR10010F-0203-20F0B-C7-N](#) [SR10010F-0204-20F0B-C7-N](#) [SR10010F-0204-20F0B-C7-N-0027](#) [SR10010F-0202-20F0B-C7-N-0027](#) [SR10010F-0205-20F0B-C7-N-0027](#) [SR10010F-0106-20F0B-C7-N-0027](#) [SR10010F-0203-20F0B-C7-N-0027](#) [SR10010F-0205-20F0A-C7-N-0027](#)